



DELUXE DOUBLE ARM REPAIR STAND PRS-2

Ref. No.	Part No.	Description	Qty.	Ref. No.	Part No.	Description	Qty.
1	138	Handle grip	2	16	114S	Unthreaded lock block	3
2	103S	Handle	2	17	109S	Spring pin 5/32 x 1-1/4	3
3	107S-2	Pin with washers and circlips	4	18	112S	Lock block bolt assembly	3
4	101-3	Movable jaw	2	19	111S	Handle	3
5	468B	Jaw cover set (incl. circlips)	2	20	110S	Ball knob	3
6	102-3	Rotating shaft	2		180	Lock block assy. (#14-20)	
7	108S-2	Pin with washers and circlips	2	21	124S	"T" Support	1
8	117S-1	Revised eyebolt	2	22	123S	Pin 5/16 x 1 1/4	1
9	119S	Knurled locknut	2	23	104	Work Tray complete	1
10	118S	Adjusting barrel	2	24	125S	Base support upright	1
11	121S	Adjusting barrel pivot	2	25	131S	Nut 1/4 - 20	4
12	136	Nut 1/4 - 28	2	26	132S	Washer 3/16"	4
	122S	Linkage assembly (#8-12)	2	27	133S	Bolt 1/4 - 20 x 7/8	4
13	116S	Cap screw	4	28	135	Base	1
14	113S	Threaded lock block	3				
15	115S	Spring	2				

NOTE: Because of design changes made to the 100-3C Clamp, replacement of a #102-3 Rotating shaft manufactured prior to Jan. 2001 also requires replacement of the #103S Handle. A #102-3 manufactured prior to Jan. 2001 will have a protrusion (approx. 21mm x 9mm x 8mm) on the shaft. A #102-3 manufactured after Jan. 2001 will not have this protrusion.

