



DELUXE OVERSIZE SINGLE ARM REPAIR STAND PRS-3 OS
DELUXE OVERSIZE BENCH MOUNT REPAIR STAND PRS-4 OS
DELUXE WALL MOUNT REPAIR STAND PRS-4W

<u>Ref. No.</u>	<u>Part No.</u>	<u>Description</u>	<u>Qty.</u>	<u>Ref. No.</u>	<u>Part No.</u>	<u>Description</u>	<u>Qty.</u>
1	138	Handle grip	1	20	109S	Spring pin 5/32 x 1-1/4	1
2	103S	Handle	1		180	Lock block assy. (#14-20)	
3	107S-2	Pin with washers and circlips	2	21	179A	End cap	1
4	101-3	Movable jaw	1	22	128B	Bolt 7/16 - 14 x 2-1/2	1
5	468B	Jaw cover set (incl. circlips)	1	23	128-3	Washer 7/16" SAE	1
6	102-3	Rotating shaft	1	The following part is used on the PRS-4 OS only:			
7	108S-2	Pin with washers and circlips	1	24	182A	Bench support	1
8	117S-1	Eyebolt	1	The following parts are used on the PRS-3 OS only:			
9	118S	Adjusting barrel	1	25	125A	Upright	1
10	121S	Adjusting barrel pivot	1	26	105	Oversize work tray complete	1
11	136	Nut 1/4 - 28	1	27	128-5	Hex nut, 7/16 - 14	1
	122S	Linkage assembly (#8-11)		28	128-3	Washer, 7/16"	1
12	116S	Cap screw	2	29	128B	Bolt, 7/16 - 14 x 2-1/2	1
13	124A	Horizontal tube	1	30	125B	Base support	1
14	113S	Threaded lock block	1	31	131S	Nut 1/4 - 20	4
15	115S	Spring	1	32	132S	Washer 1/4" cut	4
16	114S	Unthreaded lock block	1	33	130	Base	1
17	112S	Lock block bolt assembly	1	34	133S	Cap screw 1/4 - 20 x 7/8	4
18	110S	Ball knob	1	The following part is used on the PRS-4W only:			
19	111S	Handle	1	35	196-4	Wallmount weldment	1

NOTE: Because of design changes made to the 100-3C Clamp, replacement of a #102-3 Rotating shaft manufactured prior to Jan. 2001 also requires replacement of the #103S Handle. A #102-3 manufactured prior to Jan. 2001 will have a protrusion (approx. 21mm x 9mm x 8mm) on the shaft. A #102-3 manufactured after Jan. 2001 will not have this protrusion.