



DELUXE REPAIR STANDS PRS-3 and PRS-4

Ref. No.	Part No.	Description	Qty.	Ref. No.	Part No.	Description	Qty.
1	138	Handle grip	1	18	112S	Lock block bolt assembly	1
2	103S	Handle	1	19	110S	Ball knob	1
3	107S-2	Pin with washers and circlips	2	20	111S	Handle	1
4	101-3	Movable jaw	1	21	109S	Spring pin 5/32 x 1 1/4	1
5	468B	Jaw cover set (incl. circlips)	1	22	179	End cap	1
6	102-3	Rotating shaft	1	23	128-4	Bolt 7/16 - 14 x 2	1
7	108S-2	Pin with washers and circlips	1	24	128-3	Washer 7/16" SAE	1
8	117S-1	Eyebolt	1	25	182	Bench Support	1
9	119S	Knurled locknut	1	26	125-3	Upright tube and flange	1
10	118S	Adjusting barrel	1	27	104	Work Tray complete	1
11	121S	Adjusting barrel pivot	1	28	130	Base	1
12	136	Nut 1/4 - 28	1	29	131S	Nut 1/4 - 20	4
	122S	Linkage assembly (#8-12)		30	132S	Washer 3/16" cut	4
13	116S	Cap screw	2	31	133S	Bolt 1/4 - 20 x 7/8	4
14	124-3	Horizontal tube	1	32	180	Lock block assy.	
15	113S	Threaded lock block	1				
16	115S	Spring	1				
17	114S	Unthreaded lock block	1				

NOTE: Because of design changes made to the 100-3C Clamp, replacement of a #102-3 Rotating shaft manufactured prior to Jan. 2001 also requires replacement of the #103S Handle. A #102-3 manufactured prior to Jan. 2001 will have a protrusion (approx. 21mm x 9mm x 8mm) on the shaft. A #102-3 manufactured after Jan. 2001 will not have this protrusion.

